



## **Ventam 75 Gas Safety Interlock System User Guide**

**THE AMBER "FANS OFF LIGHT" SHOULD BE ON.  
IF IT IS NOT ON, THE POWER IS TURNED OFF.**

- 1 TURN ON THE VENTILATION FAN(S). THERE IS ALWAYS AN EXTRACT FAN, BUT THERE MAY ALSO BE A FRESH AIR FAN TOO.**
- 2 THE GREEN "FANS ON" LIGHT SHOULD NOW BE ON.**
- 3 IF THE GREEN "FANS ON" LIGHT DOES NOT COME ON, INCREASE THE SPEED OF EACH FAN UNTIL THE GREEN "FANS ON" LIGHT DOES COMES ON.**
- 4 IF THE RED "EMERGENCY STOP OPERATED" LIGHT IS ON, THE GAS SYSTEM WILL NOT WORK BECAUSE ONE OF THE EMERGENCY STOP BUTTONS HAS BEEN PRESSED.  
CHECK THAT NONE OF THE EMERGENCY STOP BUTTONS IN THE KITCHEN HAVE BEEN PRESSED.  
IF A STOP BUTTON HAS BEEN PRESSED, RELEASE IT BY PULLING IT AND TWISTING IT ANTI-CLOCKWISE.  
WHEN THE RED "STOP BUTTON" LIGHT IS OFF, MOVE ON TO STEP SIX.**
- 5 PRESS THE GAS RESET PUSHBUTTON – THE GAS ON LIGHT SHOULD NOW BE ON.**
- 6 IF THE GREEN "GAS ON" LIGHT DOES NOT COME ON, CHECK THAT THE "FANS ON" LIGHT IS ON (STEPS 2 - 4) AND THEN REPEAT STEP NUMBER SIX.**
- 7 WHEN COOKING IS FINISHED, TURN OFF ALL GAS APPLIANCES AT THE APPLIANCE ISOLATION VALVES AND THEN TURN OFF THE FANS.**
- 8 THE RED EMERGENCY STOP BUTTON IS ONLY TO BE USED IN AN EMERGENCY.**

**IN THE EVENT OF AN EMERGENCY,  
THE GAS ISOLATION VALVE MUST BE CLOSED.  
ALL DOWNSTREAM BURNERS AND PILOT VALVES ON APPLIANCES  
MUST BE TURNED OFF PRIOR TO ATTEMPTING TO RESTORE THE GAS SUPPLY.  
AFTER EXTENDED SHUT-OFF, PURGE BEFORE RESTORING GAS.**